




Catalogo 2009

l a z z a r i n i



Roma


Radiatore da bagno in acciaio con collettori laterali 40x30 mm e tubi tondi orizzontali da 25 mm. Roma viene fornito anche in versione solo elettrico e con attacchi 50 mm.




842




1230



1512



1785



BIANCO

CROMATO

DIRITTO

Altezza mm	largh. mm	inter. mm	peso kg	acqua lit	watt Dt 50°C	resist. watt	codice
842	450	400	7,2	3,6	360	300	OR0000084045
842	500	450	7,8	3,9	389	300	OR0000084050
842	550	500	8,5	4,2	418	300	OR0000084055
842	600	550	9,1	4,5	449	300	OR0000084060
1230	450	400	9,5	5,6	491	500	OR00000123045
1230	500	450	10,0	6,1	542	500	OR00000123050
1230	550	500	10,6	6,7	592	700	OR00000123055
1230	600	550	11,4	7,2	644	700	OR00000123060
1512	450	400	11,6	6,7	737	700	OR00000151045
1512	500	450	12,3	7,2	807	700	OR00000151050
1512	550	500	13,2	7,8	876	700	OR00000151055
1512	600	550	14	8,4	945	1000	OR00000151060
1512	750	700	16,6	9,4	1190	1000	OR00000151075
1785	450	400	15,6	8,4	832	1000	OR00000178045
1785	500	450	16,9	9,2	908	1000	OR00000178050
1785	550	500	18,3	10,0	982	1000	OR00000178055
1785	600	550	20,0	10,9	1060	1000	OR00000178060
1785	750	700	24,6	13,7	1335	1000	OR00000178075

Altezza mm	largh. mm	inter. mm	peso kg	acqua lit	watt Dt 50°C	resist. watt	codice
842	500	450	7,8	3,9	292	300	OR00001084050
1230	500	450	10,0	6,1	406	500	OR00001123050
1230	600	550	11,4	7,2	483	500	OR00001123060
1512	500	450	12,3	7,2	605	500	OR00001151050
1512	600	550	14	8,4	709	700	OR00001151060
1512	750	700	16,6	9,4	893	700	OR00001151075
1785	500	450	16,9	9,2	681	700	OR00001178050
1785	600	550	20,0	10,9	795	700	OR00001178060
1785	750	700	24,6	13,7	1001	1000	OR00001178075

CURVO

842	500	450	7,8	3,9	389	300	OR00010084050
1230	500	450	10,0	6,1	542	500	OR00010123050
1230	600	550	11,4	7,2	644	700	OR00010123060
1512	500	450	12,3	7,2	807	700	OR00010151050
1512	600	550	14,0	8,4	945	1000	OR00010151060
1512	750	700	16,6	9,4	1190	1000	OR00010151075
1785	500	450	16,9	9,2	908	1000	OR00010178050
1785	600	550	20,0	10,9	1060	1000	OR00010178060
1785	750	700	24,6	13,7	1335	1000	OR00010178075

842	500	450	7,8	3,9	292	300	OR00011084050
1230	500	450	10,0	6,1	406	300	OR00011123050
1230	600	550	11,4	7,2	483	500	OR00011123060
1512	500	450	12,3	7,2	605	500	OR00011151050
1512	600	550	14,0	8,4	709	700	OR00011151060
1512	750	700	16,6	9,4	893	700	OR00011151075
1785	500	450	16,9	9,2	681	700	OR00011178050
1785	600	550	20,0	10,9	795	700	OR00011178060
1785	750	700	24,6	13,7	1001	1000	OR00011178075